



thin gap

LS SERIES FRAMELESS MOTOR KIT

HIGH TORQUE-TO-WEIGHT RATIO | LIGHT-WEIGHT AND LOW-INERTIA | HIGHLY EFFICIENT
RING ARCHITECTURE | ZERO COGGING FOR PRECISION MOVEMENT | SCALABLE IN SIZE AND POWER

Data Sheet Model Number:

LSI 25-10

ThinGap's LS Line includes numerous high performance brushless permanent magnet motors. The LS line targets lower speed, high precision applications such as gimbals, optics, and precision robotics. The highest torque density with high power capability and low thermal resistance.

Winding Independent Parameter Table

Continuous Parameters	Units	Value
Continuous Torque @ Max Speed	mN-m	16.3
Max Continuous Speed	RPM	6,370
Max Continuous Power	W	11
Peak Parameters @ Max Speed	Units	Value
Peak Torque (1 sec)	mN-m	44.2
Peak Power (1 sec)	W	29
Peak Torque (3 sec)	mN-m	28.6
Peak Power (3 sec)	W	19
Mechanical Parameters	Units	Value
Number of Magnetic Poles	ea	8
Outer Diameter	mm	25
Through Hole Diameter	mm	11.96
Axial Height	mm	10
Rotor Inertia	kg-m ²	8.21E-07
Rotor Mass	kg	0.012
Stator Mass	kg	0.010
Part Set Mass	kg	0.022
Temperature Parameters	Units	Value
Max Stator Temperature	°C	130
Max Rotor Temperature	°C	85
Thermal Resistance	°C/W	14.596



ThinGap's LS Line of Brushless Motors
For low speed, high precision applications such as gimbals, optics, and precision robotics. Highest torque density with high power capability.
Available in sizes 25mm to 267mm.

Torque and Mechanical Speed

Continuous rated torque of up to 16.3 N-m and a rated speed of up to 6370 RPM.

Motor Controller Recommendation

Standard 3-Phase Controller
High Frequency PWM power input

Resources for Integration

Space-claim CAD files at:
www.thingap.com

Complete Mechanical drawings available upon request

Winding dependent Parameter Table

		WYE SERIES	WYE PARALLEL*	DELTA PARALLEL*
Electrical Parameters	Units	Value	Value	Value
Required Motor Voltage @ Max Speed	V _{pkl-l}	6.9	3.5	2.0
Max Continuous Phase Current	A _{RMS}	2.1	4.2	7.3
Peak Phase Current (1 sec)	A _{RMS}	5.3	10.5	18.3
Peak Phase Current (3 sec)	A _{RMS}	3.5	7.0	12.12
Motor Resistance @ 20°C	Ω	0.81	0.20	0.07
Motor Resistance @ Max Temperature	Ω	1.14	0.29	0.09
Terminal Inductance	μH	7.46 ± 16%	1.87 ± 16%	0.62 ± 16%
Electrical Frequency @ Max Speed	Hz	425	425	425
Motor Constants	Units	Value	Value	Value
Voltage Constant (l-l)	V _{pkl-l} /rad/s	0.007	0.004	0.002
Voltage Constant (l-l)	V _{pkl-l} /kRPM	0.755	0.378	0.218
Torque Constant	N-m/A _{RMS}	0.009	0.004	0.003
Motor Constant	N-m/√W	0.008	0.008	0.008

*WYE Parallel and Delta Parallel winding option not available off-the-shelf; may be ordered as a special configuration.